

# TÜV-Verband Welding Consumable Leaflet

## according to TÜV-Verband Technical Leaflet 1153 and DIN EN 14532

|                                                                                                                                                                                                                                                                                                                                        |    |                                                                                                                                   |                                                                                 |                    |                                                                                      |  |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----|-----------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------|--------------------|--------------------------------------------------------------------------------------|--|
|                                                                                                                                                                                                                                                       |    | 1 Manufacturer/Supplier<br>STANVAC INTERNATIONAL LIMITED<br>Plott No. 551, Pace City II, Sector 37<br>IND 122001 Haryana, Gurgaon |                                                                                 |                    | 2 Number:<br>20192.00<br>08.11.2024                                                  |  |
| 3 Welding consumable*:                                                                                                                                                                                                                                                                                                                 |    | Stabelektrode                                                                                                                     |                                                                                 |                    |                                                                                      |  |
| 4 Trade name*:                                                                                                                                                                                                                                                                                                                         |    | STAVINOX 7018 S                                                                                                                   |                                                                                 |                    |                                                                                      |  |
| 7 Type*:                                                                                                                                                                                                                                                                                                                               |    | EN ISO 2560-A - E 42 5 B 4 2 H5                                                                                                   |                                                                                 |                    |                                                                                      |  |
| 11 Diameter range:                                                                                                                                                                                                                                                                                                                     |    | 2,5 - 4,0 mm                                                                                                                      |                                                                                 |                    |                                                                                      |  |
| 12 Auxiliary materials:                                                                                                                                                                                                                                                                                                                |    | ---                                                                                                                               |                                                                                 |                    |                                                                                      |  |
| 13 The validity is certified by the appearance of the welding consumable leaflet in the welding consumables portal.                                                                                                                                                                                                                    |    |                                                                                                                                   |                                                                                 |                    |                                                                                      |  |
| 15 Materials and postweld heat treatment                                                                                                                                                                                                                                                                                               |    |                                                                                                                                   |                                                                                 |                    |                                                                                      |  |
| Pos                                                                                                                                                                                                                                                                                                                                    | Wb | Group / Material 1                                                                                                                | Text                                                                            | Group / Material 2 | Remarks                                                                              |  |
|                                                                                                                                                                                                                                                                                                                                        | U  | Gruppe 1.1                                                                                                                        |                                                                                 |                    |                                                                                      |  |
|                                                                                                                                                                                                                                                                                                                                        | U  | Gruppe 1.2                                                                                                                        |                                                                                 |                    |                                                                                      |  |
| 16 Material groups acc. to CR ISO 15608                                                                                                                                                                                                                                                                                                |    |                                                                                                                                   |                                                                                 |                    |                                                                                      |  |
| 21 Root weldability:                                                                                                                                                                                                                                                                                                                   |    | verified                                                                                                                          |                                                                                 |                    |                                                                                      |  |
| 23 Wall thickness:                                                                                                                                                                                                                                                                                                                     |    | max. 40 mm                                                                                                                        |                                                                                 |                    |                                                                                      |  |
| 24 Type of current and polarity:                                                                                                                                                                                                                                                                                                       |    | G+                                                                                                                                |                                                                                 |                    |                                                                                      |  |
| 25 Welding position according to DIN EN ISO 6947:1997-05: PA, PB, PC, PD, PE, PF                                                                                                                                                                                                                                                       |    |                                                                                                                                   |                                                                                 |                    |                                                                                      |  |
| 26 Highest operating temperature in the short-term range as for parent metal, but not higher than:                                                                                                                                                                                                                                     |    |                                                                                                                                   |                                                                                 | 350 °C             |                                                                                      |  |
| 27 Highest operating temperature in the long-term range max.:                                                                                                                                                                                                                                                                          |    |                                                                                                                                   |                                                                                 | --- °C             |                                                                                      |  |
| 28 Lowest operating temperature/as for parent metal, but not lower than:                                                                                                                                                                                                                                                               |    |                                                                                                                                   |                                                                                 | -50 °C             |                                                                                      |  |
| 29 Design stress value/as for parent metal:                                                                                                                                                                                                                                                                                            |    |                                                                                                                                   | wie Grundwerkstoff                                                              |                    |                                                                                      |  |
| 30 For use in the long-term range:                                                                                                                                                                                                                                                                                                     |    |                                                                                                                                   | ---                                                                             |                    |                                                                                      |  |
| 31 Resistance to intergranular corrosion proven in accordance with:                                                                                                                                                                                                                                                                    |    |                                                                                                                                   | ---                                                                             |                    |                                                                                      |  |
| 32 Remarks :<br>---                                                                                                                                                                                                                                                                                                                    |    |                                                                                                                                   |                                                                                 |                    |                                                                                      |  |
| 33 The approval test for the welding consumable was carried out on the basis of TÜV-Verband Technical Leaflet 1153 and DIN EN 14532. If no conflicting test principles are stated under heading 32 – Remarks –, this welding consumable is suitable for use according to the Pressure Equipment Directive 2014/68/EU, Annex I Point 4. |    |                                                                                                                                   |                                                                                 |                    |                                                                                      |  |
| 34 Explanations                                                                                                                                                                                                                                                                                                                        |    | A tempered<br>L solution annealed and quenched<br>N normalized                                                                    | S stress-relieved<br>St stabilized<br>U non-annealed<br>V hardened and tempered | W soft annealed    | G+ direct current plus pole<br>G- direct current minus pole<br>W alternating current |  |
| 35 Compiled in accordance with the data of:                                                                                                                                                                                                                                                                                            |    |                                                                                                                                   |                                                                                 | TÜV Rheinland      |                                                                                      |  |
| The duplication, circulation, copy and complete edition by photomechanical or similar techniques remain subject to the editor's approval even if only used in extracts. Editor: TÜV-Verband e. V.<br>Distribution: TÜV-Media GmbH, Am Grauen Stein, 51105 Köln - Unternehmensgruppe TÜV Rheinland Group                                |    |                                                                                                                                   |                                                                                 |                    |                                                                                      |  |